


AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A gear drive mechanism with an anti-rattle device, comprising:
 - a first gear rotatable about a first axis,
 - a second gear rotatable about a second axis, wherein the second gear meshes with the first gear, and the second axis is located at a predetermined distance from the first axis,
 - a first friction disk having a first friction rim surface that is rotationally coupled to the first gear and has a first frusto-conical shape, and
 - a second friction disk having a second friction rim surface that is rotationally coupled to the second gear and has a second frusto-conical shape,
 - wherein the first friction rim surface and the second friction rim surface are in ~~mutual~~ circumferential contact with each other and thereby enabled to transmit a friction-based torque between each other, wherein one of the first and second friction rim surfaces is elastically biased against the other friction rim surface.
2. (Previously Presented) The gear drive mechanism of claim 1, wherein at least one of the first and second friction disks comprises a friction wheel that is attached to one side of the respective one of the first and second gears.
3. (Previously Presented) The gear drive mechanism of claim 1, wherein the first and second frusto-conical shapes have respective first and second median radii, and wherein said first and second median radii are equal to respective pitch circle radii of the first and second gears.

{W:\03193\000M886000\00819793.DOC  }

4. (Original) The gear drive mechanism of claim 3, wherein said-frusto-conical shapes have cone angles of substantially 25°
5. (Previously Presented) The gear drive mechanism of claim 3, wherein the friction rim surface that is biased against the other is elastically biased with a pre-tensioning force acting in a direction that causes an increased contact pressure between the first and second friction rim surfaces.
6. (Original) The gear drive mechanism of claim 5, wherein said pre-tensioning force is directed axially.
7. (Original) The gear drive mechanism of claim 6, wherein the biased one of said first and second friction rim surfaces is formed on an outer circumference of a dish-shaped spring disc.
8. (Previously Presented) The gear mechanism of claim 1, wherein the first and second discs are ring shaped disks that are coaxially arranged on, respectively, the first and second gears.
9. (Original) The gear mechanism of claim 1, wherein the first and second friction rim surfaces are hardened.
10. (Original) The gear mechanism of claim 1, wherein the first and second friction rim surfaces are provided with a coating.
11. (Original) The gear mechanism of claim 1, wherein the first friction rim surface comprises two first parts arranged, respectively, on opposite sides of the first gear, and wherein the second friction rim surface comprises two second parts arranged, respectively, on opposite sides of the second gear.

{W:\03193\000M886000\00819793.DOC 172711 172712 172713 172714 172715 172716 172717 172718 172719 172720 172721 172722 172723 172724 172725 172726 172727 172728 172729 172730 172731 172732 172733 172734 172735 172736 172737 172738 172739 172740 172741 172742 172743 172744 172745 172746 172747 172748 172749 172750 172751 172752 172753 172754 172755 172756 172757 172758 172759 172760 172761 172762 172763 172764 172765 172766 172767 172768 172769 172770 172771 172772 172773 172774 172775 172776 172777 172778 172779 172780 172781 172782 172783 172784 172785 172786 172787 172788 172789 172790 172791 172792 172793 172794 172795 172796 172797 172798 172799 172800 172801 172802 172803 172804 172805 172806 172807 172808 172809 172810 172811 172812 172813 172814 172815 172816 172817 172818 172819 172820 172821 172822 172823 172824 172825 172826 172827 172828 172829 172830 172831 172832 172833 172834 172835 172836 172837 172838 172839 172840 172841 172842 172843 172844 172845 172846 172847 172848 172849 172850 172851 172852 172853 172854 172855 172856 172857 172858 172859 172860 172861 172862 172863 172864 172865 172866 172867 172868 172869 172870 172871 172872 172873 172874 172875 172876 172877 172878 172879 172880 172881 172882 172883 172884 172885 172886 172887 172888 172889 172890 172891 172892 172893 172894 172895 172896 172897 172898 172899 172900 172901 172902 172903 172904 172905 172906 172907 172908 172909 172910 172911 172912 172913 172914 172915 172916 172917 172918 172919 172920 172921 172922 172923 172924 172925 172926 172927 172928 172929 172930 172931 172932 172933 172934 172935 172936 172937 172938 172939 172940 172941 172942 172943 172944 172945 172946 172947 172948 172949 172950 172951 172952 172953 172954 172955 172956 172957 172958 172959 172960 172961 172962 172963 172964 172965 172966 172967 172968 172969 172970 172971 172972 172973 172974 172975 172976 172977 172978 172979 172980 172981 172982 172983 172984 172985 172986 172987 172988 172989 172990 172991 172992 172993 172994 172995 172996 172997 172998 172999 173000 173001 173002 173003 173004 173005 173006 173007 173008 173009 173010 173011 173012 173013 173014 173015 173016 173017 173018 173019 173020 173021 173022 173023 173024 173025 173026 173027 173028 173029 173030 173031 173032 173033 173034 173035 173036 173037 173038 173039 173040 173041 173042 173043 173044 173045 173046 173047 173048 173049 173050 173051 173052 173053 173054 173055 173056 173057 173058 173059 173060 173061 173062 173063 173064 173065 173066 173067 173068 173069 173070 173071 173072 173073 173074 173075 173076 173077 173078 173079 173080 173081 173082 173083 173084 173085 173086 173087 173088 173089 173090 173091 173092 173093 173094 173095 173096 173097 173098 173099 173100 173101 173102 173103 173104 173105 173106 173107 173108 173109 173110 173111 173112 173113 173114 173115 173116 173117 173118 173119 173120 173121 173122 173123 173124 173125 173126 173127 173128 173129 173130 173131 173132 173133 173134 173135 173136 173137 173138 173139 173140 173141 173142 173143 173144 173145 173146 173147 173148 173149 173150 173151 173152 173153 173154 173155 173156 173157 173158 173159 173160 173161 173162 173163 173164 173165 173166 173167 173168 173169 173170 173171 173172 173173 173174 173175 173176 173177 173178 173179 173180 173181 173182 173183 173184 173185 173186 173187 173188 173189 173190 173191 173192 173193 173194 173195 173196 173197 173198 173199 173200 173201 173202 173203 173204 173205 173206 173207 173208 173209 173210 173211 173212 173213 173214 173215 173216 173217 173218 173219 173220 173221 173222 173223 173224 173225 173226 173227 173228 173229 173230 173231 173232 173233 173234 173235 173236 173237 173238 173239 173240 173241 173242 173243 173244 173245 173246 173247 173248 173249 173250 173251 173252 173253 173254 173255 173256 173257 173258 173259 173260 173261 173262 173263 173264 173265 173266 173267 173268 173269 173270 173271 173272 173273 173274 173275 173276 173277 173278 173279 173280 173281 173282 173283 173284 173285 173286 173287 173288 173289 173290 1732

12. (Currently Amended) A gear drive mechanism with an anti-rattle device, comprising:
- a first gear rotatable about a first axis and having a first retaining feature,
 - a second gear rotatable about a second axis, wherein the second gear meshes with the first gear, and the second axis is located at a predetermined distance from the first axis, the second gear having a second retaining feature,
 - a first friction disk having a central opening and a first friction rim surface that is rotationally coupled to the first gear by receiving the first retaining feature in the central opening, the first friction disk having a first frusto-conical shape, and
 - a second friction disk having a central opening and a second friction rim surface that is rotationally coupled to the second gear by receiving the second retaining feature in the central opening, the second friction disk having a second frusto-conical shape,
- wherein the first friction rim surface and the second friction rim surface are in ~~mutual~~ circumferential contact with each other and thereby enabled to transmit a friction-based torque between each other, wherein one of the first and second friction rim surfaces forms an elastic interface with the other friction rim surface.
13. (Previously Presented) The gear drive mechanism of claim 12, wherein the first and second retaining features comprise protrusions that extend outwardly from the respective first and second gears and are received in the central openings of the first and second friction disks.